

## CIRCLULAR PRESTIGE REVOLVING DOOR



### Attention to Detail and Quality

#### Bespoke design

Circular Prestige revolving doors offer an unbeatable combination of custom design and attention to detail and quality. Using the very best materials and durable construction methods, these doors provide impressive, energy-efficient entrances to suit any building.

All Prestige revolving doors feature an internal stainless steel framework for maximum strength and durability, allowing a much greater range of sizes than with an inferior aluminum framework. This framework can be overclad with a wide variety of materials to produce an outstanding finish.

The Circular Prestige is available with 2, 3 or 4 door leaves and with diameters up to 3000mm. All sizes are available in manual, semi- or fully-automatic versions and can be supplied with heights in excess of 9 metres. As an option the Circular Prestige revolvers can have a security function with swipe cards.

### TECHNICAL DATA.

<b>Product Reference:</b>	CIRCULAR PRESTIGE REVOLVING DOOR
<b>Material:</b>	Glass Overclad stainless steel frame for added durability and strength
<b>Number of wings:</b>	Two Wing Three Wing Four Wing
<b>Operation:</b>	Manual Semi-Automatic (Push & Go) Fully Automatic Security mode with controlled access
<b>Diameter:</b>	1800mm – 3000mm. Available in 1mm increments
<b>Internal Height:</b>	3000mm – 9000mm+. Available in 1mm increments
<b>Clear Opening:</b>	720mm – 2060mm* *Dependent on door configuration and diameter
<b>Locking:</b>	Manual Automatic (Semi-Automatic & Fully Automatic Versions Only)

<b>Glazing:</b>	Singled Glazed/Double Glazed Clear Low Iron Coloured Fritted Special Glazing Options
<b>Canopy:</b>	50mm +. Available in 1mm increments Please contact Bauporte for minimum heights if lighting or hot air units are required.
<b>Surface Finishes:</b>	Stainless Steel Polyester Powder Coated Special Finishes on request
<b>Accessories:</b>	Night Security Screens or Night Security Wall Matting, Water Drainage Reservoir Heaters integrated into the mat well RC2, RC3, RC4 and PAS24:2016 Options Available
<b>Push Bars:</b>	Vertical or Horizontal Handles are available
<b>Safety:</b>	Designed, Manufactured and installed to EN 16005
<b>Power Supply:</b>	230 V/50 Hz (Semi-Automatic & Fully Automatic Only)
<b>Drive Unit:</b>	Canopy installation, minimum canopy height 350mm Underfloor Drive Unit (Semi-Automatic & Fully Automatic Only) Pit size 1200 x 400x400mm (L x W x D)
<b>Warranties:</b>	Two Years or Lifetime with service contract* *Please contact Bauporte for further information
<b>Construction:</b>	Fixed curved drum walls will be constructed from welded through stainless steel profiles, which are covered with 2mm aluminum sheeting or chosen special finish. Glazed curved drum walls formed from clear curved 12mm glass in one piece over the full height of the door and divided by the midstyle. No bottom glazing profiles, the glazing fits directly into the floor construction. The rotating part will have door leaves constructed out of a welded through SS structure, which will be covered with aluminum sheets or chosen special finish. In the center, there is a central post of Stainless steel connecting the top-part and bottom-part. Diameter of the post is 60mm. Glazing is clear flat 12mm toughened glass. The profiles around each door panel are 27mm high. Door leaves are provided with single brushes on all edges.

[www.bauporte.com](http://www.bauporte.com)

BV Bauporte Design Entrances  
Zandsteen 14, 2132 MR Hoofddorp,  
Netherlands, Postbus 558,  
2130 AN Hoofddorp  
Tel: +31 (0)85 066 1203  
Sales: [sales@bauporte.com](mailto:sales@bauporte.com)

Bauporte Doors UK Ltd  
Office 212, Dowgate House,  
14-16 Dowgate Hill, London  
EC4R 2SU  
Tel: +44 (0)20 3411 5023  
Sales: [sales@bauporte.com](mailto:sales@bauporte.com)

Making an entrance 