

# Product Data Sheet

## Seamsil® Base Coat



**sharmans**  
Seamsil®  
cut edge

### Product Description

**Seamsil Base Coat is a single pack, highly versatile silicone based material designed for use in a wide range of new and remedial building applications.**

#### Uses

- Used as part of with the Seamsil Cut Edge Corrosion system for the upgrading of existing ageing and/or corroded steel profiled roofing
- Used as a preparation coat (where required) as part of the Delcote Roof Coating system.

### Characteristics/Advantages

- Seamsil Base Coat is tough, extremely flexible, ready to use and cure to form an elastic seal with excellent adhesion to most substrates.
- Seamsil Base Coat has superb weathering characteristics, being unaffected by UV, extremes of weather or temperature
- The unusually high durability and flexibility, ensures Seamsil Base Coat continues to give optimum performance after many years of exposure in the most aggressive environments.

### Product Information

Chemical Base	Silicone Coating in a Spirit Carrier
Packaging	5kg Containers
Colour	Base Coat: Grey
Shelf Life	12 months
Storage Information	Store in a cool, well ventilated, frost free area
Specific Gravity	1.22
Shore A Hardness	20 (approx.)
Time to Full Cure	10-14 days
Solids Content	By volume: 80%
Movement Accommodation	+/- 50%
Elongation at Break	750%
Tensile Strength	1.6 N/mm <sup>2</sup>

### Application Information

Application Temperature Range	+3°C to +60°C
Dew Point	Surface to be 2°C above dew point



**sharmans**  
gutter & roof refurbishment systems